



Aachener Chemische Werke

Gesellschaft für glastechnische Produkte und Verfahren mbH
Ein Unternehmen der Chemetall-Gruppe

Adenauerstraße 20 · Europark C 3 ; D-52146 Würselen ; Telefon +49 2405 4497-0 ; Telefax +49 2405 4497-30
<http://www.acw-info.com> ; Email : acw@chemetall.com

Product information

Acecut 5503

ACECUT 5503 is a completely evaporating cutting fluid for glass cutting. It is recommended when:

- cutting coated glass
- cutting automotive glass (X-Y)
- cutting float glass on-line
- cutting mirror glass

It can also be used when generally cutting glass up to approx. 10 mm.

Specification

Density:	0.769 - 0.783 g/ml	DIN 51757 (20 °C)
Refractive index:	1.428 - 1.437	DIN 51432 (20 °C)
pH (conc.):	5 - 7	pH-Indicator strips
Viscosity:	1.2 - 2.5 mPas	DIN 54453 (20 °C)

Handling

ACECUT 5503 is classified and labelled in accordance with EC directives or respective national laws as "harmful". We recommend the use of suitable protective gloves. For more safety information please see the Material Safety Data Sheet.

Storage

Stored in well closed containers at temperatures between 5 and 40 °C the minimum shelf life of ACECUT 5503 is 1 year.